

Wattyl Forestwood Deck and Furniture Oil

Page 1 of 3

DESCRIPTION

- Wattyl Forestwood Deck and Furniture Oil is an oil that will enhance the natural beauty of timber decks and garden furniture. It will highlight the natural grain, colour and texture of the timber and is versatile and easy to use.

PRINCIPAL CHARACTERISTICS

- Ideal for use on most decking and garden furniture timbers.
- Ideal for rough sawn and smooth timber or over similar oil stains.
- It adds colour to the timber but allows the grain to show through.
- Protects timber from mould and fungus.

COLOURS AND GLOSS

- Available in Natural Pine, Natural Teak, Natural Kwila.
- Matt oiled look.

BASIC DATA

- **Surface dry** 4 to 8 hours
- **Recoat** 24 hours (minimum)
- **Fully cured** Allow minimum 24 hours drying before subjecting to light foot traffic: ensure stained outdoor furniture is dry before using.
All figures are quoted at 20°C and 65% relative humidity. Drying will take longer at lower temperatures or higher relative humidity. Drying will take longer over less porous or previously stained or sealed timber. Drying may take longer on some species such as tannin rich cedar and tallowwood due to varying timber compositions. Do not apply if rain is likely within 16 hours.
- **Coverage per coat** 4 - 12m²/L depending on porosity and texture of the surface.
- **Number of coats** 2
- **Thinning** Not normally required. Thin sparingly using Mineral Turpentine if necessary
- **Clean Up** Clean all equipment thoroughly with Mineral Turpentine away from drains.
- **VOC** >300g/L as per EC-07-09

RECOMMENDED SUBSTRATE CONDITIONS AND TEMPERATURE

- Suitable for use on exterior bare timber including Kwila, Vitex, Redwood, Treated Pine, Tallowwood, Brushbox, Merbau and Jarrah; or over similar weathered oil or penetrating stain finishes.
- Ideal for all smooth or rough sawn timber, decks, beams, pergolas and outdoor furniture.
- Not suitable for previously painted or varnished timber unless it is sanded back to bare timber.
- Not suitable for use on non-timber or drive-on surfaces.
- Do not use on surfaces that have been previously painted.
- Application should not be carried out if the air temperature or the substrate temperature is below 10°C or above 35°C. The temperature must not fall below 10°C during the drying process. Do not apply when dew is likely with 4 hours.

INSTRUCTIONS FOR USE

- On new timber allow dense and resinous timbers such as Kwila, Merbau, Vitex, Teak, Jarrah and other hardwoods to weather 4-6 weeks prior to coating.
- Allow LOSP treated pine and smooth (dressed) surfaces to weather for two weeks to lose their polished surface and improve oil

uptake.

- Mill glaze must also be removed from timber by sanding to allow penetration and adhesion.
- Ensure timber is clean, dry and free from dirt, grease, oil, wax and other surface contaminants by cleaning thoroughly with Wattyl Deck & TimberPrep according to label instructions.
- If mould is present, remove as much mould growth as possible by scraping and stiff brushing and apply Wattyl Anti-MouldPrep according to label instructions.
- Rinse entire surface with clean water and allow to dry thoroughly.
- Stir Wattyl Forestwood Deck and Furniture Oil thoroughly before use and regularly during use with a broad, flat stirrer to ensure a uniform colour.
- For added colour consistency mix and box together all cans on site before use.
- Apply two coats using a brush or speed brush paying particular attention to exposed edges and end grain.
- Partly used cans of Wattyl Forestwood Deck and Furniture Oil should be used within 3 months.
- Allow to dry 24 hours between coats.
- Resist the temptation to apply excess oil, to be effective oils must penetrate the timber, not remain on the surface.
- Rags used with this product constitute a fire hazard and should be soaked in water overnight before disposal.

MAINTENANCE

- Wattyl Forestwood Deck and Furniture Oil must be regarded as a maintainable coating and re-staining should be conducted every summer, or as soon as the timber shows signs of weathering due to exposure.
- Clean surfaces using Wattyl Deck and TimberPrep before re-staining. Spot stain bare areas, allow to dry overnight and then apply one full coat to the whole area.
- Darker colours will attract more heat and the interval between re-staining may be reduced.
- Regular (six monthly) maintenance is recommended using Wattyl Anti-mould Prep. It kills existing mould growth, loosens it from the surface preventing recontamination.

SAFETY DATA

- **Caution** Provide adequate ventilation during use.
- **Spills and Disposal** Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local Council regarding the disposal of empty paint containers. Empty paint containers should be left open in a well ventilated area to dry out. When dry, recycle steel containers via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may vary between local authorities.
- **M.S.D.S.** A Material Safety Data Sheet (M.S.D.S.) is available on request.
- **First Aid:**
If swallowed **do not** induce vomiting. Give plenty of water to drink. Contact a doctor or the Poisons Information Centre. Phone 0800 764766 (New Zealand).
If in eyes, hold eyes open and flood with water for at least 15 minutes. Contact a doctor if any irritation occurs.
If on skin remove contaminated clothing, wash skin thoroughly with soap and water or a proprietary skin cleanser. Do not use solvents.
If affected by inhalation remove person to fresh air. If breathing difficulties persist or occur later, contact a doctor.

1. This information is provided with respect to the listed Wattyl products. Wattyl recommends that:

(a) The user should check the date of printing, and if more than 24 months have elapsed, should verify with our nearest sales office that the information is still current. (b) you review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (c) the product be used only in accordance with the information provided by Wattyl; (d) the product be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (e) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in this technical data sheet was prepared using information gathered during product development. While Wattyl endeavours to update this information and maintain the accuracy and currency of its contents, Wattyl cannot guarantee that the information provided is wholly comprehensive.

3. Wattyl recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Wattyl Office.

4. Because we cannot control the way these products may be used, or the conditions they may be exposed to, we can give no express guarantees in respect of these products or their performance. However certain guarantees may be implied by law.

ADDITIONAL DATA

- Wattyl Forestwood Deck and Furniture Oil will assist in retaining the natural colour of the timber but this will naturally fade and grey. When this occurs, further coats of Wattyl Forestwood Deck and Furniture Oil may be applied.
 - Available in 1L, 5L and 10L containers.
 - For further information, contact the Wattyl Information Helpline, Phone 0800 735 551.
-

1. This information is provided with respect to the listed Wattyl products. Wattyl recommends that:

(a) The user should check the date of printing, and if more than 24 months have elapsed, should verify with our nearest sales office that the information is still current. (b) you review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (c) the product be used only in accordance with the information provided by Wattyl; (d) the product be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (e) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in this technical data sheet was prepared using information gathered during product development. While Wattyl endeavours to update this information and maintain the accuracy and currency of its contents, Wattyl cannot guarantee that the information provided is wholly comprehensive.

3. Wattyl recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Wattyl Office.

4. Because we cannot control the way these products may be used, or the conditions they may be exposed to, we can give no express guarantees in respect of these products or their performance. However certain guarantees may be implied by law.

Wattyl (N.Z.) Limited, P. O. Box 1545, Auckland, 1.

WATTYL (NZ) LTD

Phone 09 820 6700

INFORMATION HELP LINE: 0800 735551 (New Zealand)

Fax 09 820 6572